



KOMORI LITHRONE LS 40-5 HC

Reference	21036027
Type	Sheetfed Offset/Offset a foglio
Manufacturer	Komori
Model	LITHRONE LS 40-5 HC
Year	2003
Serial Number	128
N.of Impressions	130

[REQUIRE MORE INFO-QUOTATION](#)

[VIEW DETAILS-GALLERY-VIDEO](#)

Accessories

- PQC: console for ink, axial, circumferential diagonal remote control
- AMR (Automatic Make Ready): automatic preset for pressure, paper size and thickness setting
- KMS : Komori Management System
- KHS : Komori High Performance System
- PDC : Auto Tracking Color Control
- Pile alignment on feeder
- Micrometric adjustment of the lateral pull pay by touch panel +/- 3 mm.
- Optical fiber precision photocell system for front and side control + safety photocell for the sheet in advance
- Paper deformation compensator placed on the infeed cylinder with remote control
- Mechanical sheet stop in case of misregistration or crooked sheet
- Feeler foot with double ionizing antistatic blower: for a good sheet separation on the back side of the pile
- Antistatic on feeder
- Preloader on feeder
- Double sheet electronic detection
- Speed Reduction : dampening roller with reduced peripheral speed
- Komorimatic damping
- Technotrans Beta.c 200 ink temp control combined with damping refrigeration + Automix
- FAPC fully automatic plate change
- Inks de-clutching device on 1° and 5° printing units
- Automatic roller wash-up device
- Automatic blanket washers with cloth
- Automatic impression cylinder washers with cloth
- Skeleton Transfer cylinders with with manual adjustment movement, pick-up pad grippers with vacuum system

- Double diameter impression cylinders
- Varnishing unit, Tresu chambered doctor blade system, with anilox roller
- TRESU AQUA L10 Coating Circulator
- Extended delivery 2 meters
- Grafix Digitronic powder spray
- IR/HOT AIR GraphiSet4 IVT Baldwin dryer
- Non-Stop in delivery
- Perimeter sensors in delivery
- Antistatic in delivery
- 15.000 speed/h
- Thickness Material: 0,04 / 1.0 mm