



HEIDELBERG XL75-6 P2+LX 3 (F) Hybrid

Reference	24036459
Type	Sheetfed Offset/Offset a foglio
Manufacturer	Heidelberg
Model	XL75-6 P2+LX 3 (F) Hybrid
Year	2016
Serial Number	LS001264
N.of Impressions	115

[REQUIRE MORE INFO-QUOTATION](#)

[VIEW DETAILS-GALLERY-VIDEO](#)

Accessories

- Console
 - Prinect Press Center console touch screen, axial, circumferential and diagonal register remote control, ink ductors rotation control, job memorization
 - Prinect Press Center MasterLevel
 - **Prinect Press Center Color Assistant Pro**
 - **Press Center InstantStar**
 - **Prinect Press Center InstantGate**
 - **Image Control: Spectrophotometric quality control on all the surface of the printed sheet**
- Feeder
 - Pile height sensor
 - Pneumatic side register control with integrated auto cleaning and double sheet control with direct system
 - **Non-Stop on feeder**
 - **Double sheet detector - pulling device**
 - StaticStar Compact : No. 2 Eltex ion blowers on feeder, antistatic bars on feeder and delivery
- Printing Units
 - Alcolor Vario System damping
 - Double diameter impression cylinders
 - Double diameter transfer cylinder between printing units, with Air Transfer System with possibility to adjust automatically it based on thickness of material to print
 - Roller wash-up device controlled by Prinect Press Center
 - Blanket and impression cylinders automatic washing devices by Prinect Press Center
 - **Suction brush on 1 printing unit**
 - **Autoplate PRO: Automatic plate change**

- CombiStar PRO CAN : Technotrans ink temp control combined with damping refrigeration + Alcosmart
- **Auto Protect. Protective fluid management system for the X PU inking rollers**
- **Blowing bar (anti-emulsion) on the inking units, recommended for UV and hybride X PU machines**
- **6/0 ; 1/5 Fully Automatic perfecting device**
- **N.ro 3 x DryStar IST/UV Interdeck CAN to put in all transfer positions (full flexibility)**
- **Ink.mate Technotrans Ink agitators**
- Varnishing units
 - **Varnishing unit 550 L./H., with cooking register, Tresu pressurized chambered doctor blade system, with anilox roller**
 - **Coating Star : heat coater system**
 - **One additional camera not pressured**
 - **Nro 4 anilox rollers: 120 lines (paper); 100 lines (UV); 80 lines (cardboard); 60 lines (cardboard);**
- Delivery
 - **Extended Delivery (240 cm / X3)**
 - **Non-Stop in delivery**
 - **PowderStar Weko AP 500 CANopen**
 - **CleanStar Compact : filter for powder spray suction**
 - **DryStar Combination UV CAN with 4 modules (IR/HA + HA + EOP UV + Cold Air Module) Water Cooled**
- Peripherals
 - ScrollStar : Atlas Copco compressor
 - **AirStar Pro : central air box water cooled**
- Various
 - 15.000 speed/h
 - **Technotrans Beta.t : Water refrigeration cabin for UV Dryer**
 - **Elevated 550 mm**
 - **Intercom : Microphone communication system**